

Leading the way in new innovative circuit protection



With effect from 16th March, 2026



Powering Business Worldwide

About EAT•N

Eaton is an intelligent power management company dedicated to protecting the environment and improving the quality of life for people everywhere. We provide sustainable solutions that help our customers manage electrical and mechanical power—more safely, efficiently, and reliably. By capitalizing on the global growth trends of electrification and digitalization, we are accelerating the planet's transition to renewable energy, solving the world's most urgent power management challenges, and building a more sustainable society for today and generations to come.

Eaton was founded in 1911 and has continuously evolved to meet the changing needs of industries worldwide. In 2025, our revenues reached nearly \$27.4 billion, and we serve customers in more than 160 countries. Eaton has approximately 92,000 employees globally. The company first established a presence in the Asia Pacific region in the 1970s. Since then, our presence has grown significantly, with a fast-expanding network of sales and marketing offices, manufacturing plants, service centers, and research facilities in the region.

Today, we have nearly 17,000 employees, 6 R&D centers, and operate 34 manufacturing facilities across countries and regions including China, India, Japan, South Korea, Singapore, Indonesia, Thailand, the Philippines, and Australia for all of Eaton's distinct business segments.

Operating in
160+
countries

92,000+
employees

100+
years of
experience

\$27.4
BILLION IN
SALES 2025

18,000+
patents

A legacy of innovation

We make stronger together work.*

US-focused power
distribution
and control business

Power quality and
datacenter market

Global geographic
expansion

Built scale

Extended
capabilities

Scaling
Precision



POWERWARE

MOELLER



INNOVATIVE SWITCHGEAR



greenmotion

PDI

HUYU



EXERTHERM

1979 1994

2004

2008

2013

2019 - 2021

2022-2025



We have built our capabilities and expanded through key acquisitions and partnerships...

© 2025 Eaton. All rights reserved..

Contact Eaton today to learn how the Eaton
can Transform your power Infrastructure

Visit Eaton.com/in for more information

Eaton Power Quality Pvt. Ltd. 2, EVR Street, Sedarpet Industrial Estate Pondicherry - 605111 | Tel: +91 413 2672000

Specifications subject to change without notice. ©2025 Eaton Corporation. All rights reserved.

Eaton's Product Range

Low Voltage Distribution Products

Air Circuit Breakers	PSL / IZM
Molded Case Circuit Breakers	PDC / NZM / BZMx
Disconnectors	P / PN
Mining Duty Breakers	
ATS	



Contactors

Mini Contactors & Control Relays	DILEM / DILEEM / DILER
Control Relays & Power Contactors	DILM / DILA / XTC
Vacuum Contactors	DILM / DILH / V201
4 Pole Contactors	DILMP
Capacitor Duty Contactors	DILK
DC Mill Duty Contactors	
DC Power Contactors	
Definite Purpose Contactors	



Overload Relays

Thermal Magnetic Overload Relay	ZB/ZE/ZEB
Motor Management Relay	Motor Insight, C440
Thermistor Based Overload Relays	EMT6



Motor Protection Circuit Breakers (MPCB)

MPCB with Push Button Control	PKZM01
MPCB with Rotary Handle Control	PKZM0
MPCB with Electronic Release	PKE



Low Voltage Control Products

Pilot Devices (22.5mm & 16mm)	RMQTitan (M22) / A22
Pilot Devices (30.5mm)	E30/E34/10250T
Foot & Palm Switch	FAK
Signal Towers	SL
Pressure Switches	MCS
Position Switches / Safety Switches ...	LS
Sensors	Inductive / Capacitive / Optical
Limit Switches	Precision / Mini / Metal / Metal-IP67 / Hazardous Applications



w.e.f from 16th March, 2026

Eaton's Product Range

Cam Switches & Switch - Disconnectors

Cam Switches upto 132KW.....	T
Switch-Disconnector upto 110KW/315A	P
ATEX Rated Enclosures	T/P



Electronic Relays

Safety Relay	ESR5
Safety Control Relays	Easy Safety
Timing Relays	ETR2 / ETR4
Measuring & Monitoring Relays	EMR



Automation Products

Relays	Easy500/700/800
PLC's	XC / EC4
HMI/ HMI-PLC's	XVC
Smartwire Darwin Communication System	



Motor Starters

DOL / RDOL Starter upto 32A with PKZM0	
DOL / RDOL Starter upto 32A with PKE	
Soft Starters upto 900KW.....	S8014/S8114
Variable Speed Starter	DE1
Variable Speed Drive	DG1/DF1/DV1



Enclosures

IP65, Outdoor rated Polycarbonate Opaque/Transparent ...	CI /CI-K
MCB Individual Enclosure	AE...
MCCB / Switch Disconnector	MCCB...
Fuse Enclosure	RS..



Solar Products

Air Circuit Breakers upto 4000A, 690V/800V/1140V/1500V AC
Moulded Case Circuit Breakers upto 1600A, 800V/1000V AC
Miniature Circuit Breakers upto 63A, 500V DC/1000V DC
Disconnectors upto 60A, 1000V DC rated
Disconnectors, 160A - 1400A, 1500V DC rated
Fuse & Fuse Base, 1000V DC
Inverters upto 1MW
DC Combiner Boxes
AC Switchgear



w.e.f from 16th March, 2026

Contents

Low Voltage Fuse Links & Fuse Holders

HRC Fuse Fittings & Bases	5
Low Voltage BS88 Type of Fuse Links	5 - 8
Low Voltage NH Type of Fuse Links	9

Highspeed Voltage Fuse Links

BS88 Semi-Conductor Protection, Highspeed Fuses	10 - 11
Accessories for BS88 Highspeed Fuses	12

High Voltage Fuse Links

BS Type HV Fuses for use in Air	13 - 14
HV Fuses for use in Oil	15
HV Fuses for use in PT/VT & Auxillary Transformer	15
HV Fuses for use in for HV Motor Circuits	16

Fuse Range

Low Voltage BS88 Type of Fuse Links Range	17 - 18
Highspeed Voltage Fuse Links Range	19 - 20
Medium Voltage Fuse Links	21
HV Fuses for use in Motor Circuits	22

Cross Reference Chart

Cross Reference Chart	23
-----------------------	----

Fuse Base for LV NH Type of Fuse

IS / BS Size Reference	Description	No. of Poles	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
00 / C00	Fuse Base	Single	DIN Size 00/000	160	SD00-D	690	470	3	3	O
00 / C00	Cover	Single	For holder SD00-D	160	SD00-SK*	690	#	-	3	O
00 / C00	Phase Barrier	Single	For holder SD00-D	160	SD00-PB**	690	#	-	6	O

- Price Available on request

*Kit includes Cover (3), Shroud (6)

**Barrier (2)

Fuse Fittings for LV BS Type of Fuses

IS / BS Size Reference	Tag Type	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Carton Qty.	MOQ	Delivery Class
F1	Clip on	Front	F06/NSD	20	FA20	500	200	10	10	N
		Front	F06/NSD	32	FA32	500	210	10	10	N
		Back	F06/NSD	32	FB32	500	285	10	10	N
		Busbar	F06/NSD	32	FD32	500	280	10	10	N
A2	Offset Bolted	Front	H07/F07/AAO	32	HA32	500	360	5	5	N
		Busbar	H07/F07/AAO	32	HD32	500	445	5	5	N
A3	Offset Bolted	Front	T07/BAO/KO7	63	KA63	500	480	5	5	N
		Busbar	T07/BAO/KO7	63	KD63	500	570	5	5	N
A4	Offset Bolted	Front	L14/KL14/M14	100/125	LA125	500	1335	1	1	N
		Busbar	L14/KL14/M14	100/125	LD125	500	#	1	1	N
F1	Clip on	Front (#)	F06/NSD	32	32NNSF	550	280	10	10	N
		Front	ESD	63	63ENSF	415	2180	5	5	O

Safe lock Range - Screw as wells as DIN Rail fixing (#)

Busbar / Stud Mounting

In White / Grey Body

Low Voltage BS88 - Clip on Type of Fuses

240 / 550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Breaking Capacity (kA)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ		
	E1	SMALL CLIP	240	33	2	SSD2	90	20	20	N	SS
		ON	240	33	4	SSD4	90	20	20	N	
			40	33	6	SSD6	90	20	20	N	
			240	33	10	SSD10	95	20	20	N	
			240	33	16	SSD16	100	20	20	N	
			240	33	20	SSD20	100	20	20	N	
			240	33	25	SSD25	105	20	20	O	
	F1	CLIP ON	550	80	2	NSD2	75	20	20	N	NS
		TAG	550	80	4	NSD4	75	20	20	N	
			550	80	6	NSD6	75	20	20	N	
			550	80	10	NSD10	75	20	20	N	
			550	80	16	NSD16	90	20	20	N	
			550	80	20	NSD20	90	20	20	N	
			550	80	25	NSD25	95	20	20	N	
	F2	LONG CLIP	550	80	2	ESD2	130	20	20	O	ES
		ON	550	80	4	ESD4	130	20	20	O	
			550	80	6	ESD6	130	20	20	O	
			550	80	10	ESD10	130	20	20	O	
			550	80	16	ESD16	130	20	20	O	
			550	80	20	ESD20	130	20	20	O	
			550	80	25	ESD25	140	20	20	O	
			550	80	32	ESD32	140	20	20	O	
			550	80	40	ESD40	190	20	20	O	
			550	80	50	ESD50	200	20	20	N	
			550	80	63	ESD63	210	20	20	N	

N - Normal; O - On Order

w.e.f from 16th March, 2026

Low Voltage BS88 Type of fuses

Bolted Type, 660/690 Volts range, Breaking Capacity - 80kA

660 / 690 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	A2	OFF SET TAG	660 / 690	2	2HO7-660	150	20	20	N	TIA
		CLOSED SLOT	660 / 690	4	4HO7-660	150	20	20	N	
			660 / 690	6	6HO7-660	150	20	20	N	
			660 / 690	10	10HO7-660	175	20	20	N	
			660 / 690	16	16HO7-660	175	20	20	N	
			660 / 690	20	20HO7-660	175	20	20	N	
			660 / 690	25	25HO7-660	175	20	20	N	
			660 / 690	32	32HO7-660	175	20	20	N	
	A3	OFF SET TAG	660 / 690	35	35KO7-660	240	20	20	N	TIS
		CLOSED SLOT	660 / 690	40	40KO7-660	240	20	20	N	
			660 / 690	50	50KO7-660	260	20	20	N	
			660 / 690	63	63KO7-660	260	20	20	N	
	A4	OFF SET TAG	660 / 690	80	80L14-660	480	10	10	N	TCP
		CLOSED SLOT	660 / 690	100	100L14-660	400	10	10	N	
	-	OFF SET TAG	660 / 690	125	125M14-660	#	5	5	N	TFP
		CLOSED SLOT	660 / 690	160	160M14-660	#	5	5	N	
			660 / 690	200	200M14-660	#	5	5	N	

N - Normal; O - On Order

Bolted Type, 660/690 Volts range, Breaking Capacity - 80kA

660 / 690 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B1	CENTRE TAG	660 / 690	80	80LO9-660	500	10	10	O	TC
		SINGLE SLOT	660 / 690	100	100LO9-660	460	10	10	N	
	B2	CENTRE TAG	660 / 690	125	125MO9-660	#	5	5	N	TF
		SINGLE SLOT	660 / 690	160	160MO9-660	#	5	5	N	
			660 / 690	200	200MO9-660	#	5	5	N	
	B3	CENTRE TAG	660 / 690	250	250NO9-660	#	1	1	N	TKF
		SINGLE SLOT	660 / 690	315	315NO9-660	#	1	1	N	
	C1	CENTRE TAG	660 / 690	355	355P11-660	#	1	1	O	TMF
		DOUBLE SLOT	660 / 690	400	400P11-660	2140	1	1	O	
	C2	CENTRE TAG	660 / 690	450	450R11-660	#	1	1	O	TM
		DOUBLE SLOT	660 / 690	500	500R11-660	2495	1	1	O	
			660 / 690	560	560R11-660	2815	1	1	O	TTM
			660 / 690	630	630R11-660	2990	1	1	O	

N - Normal; O - On Order
- Price Available on request

w.e.f from 16th March, 2026

Low Voltage BS88 Type of fuses

Bolted Type, 550 Volts range, Breaking Capacity - 80kA

550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	-	OFFSET TAG	550	2	NITD2	115	20	20	N	NIT
		OPEN SLOT	550	4	NITD4	115	20	20	N	
			550	6	NITD6	115	20	20	N	
			550	10	NITD10	115	20	20	N	
			550	16	NITD16	115	20	20	N	
			550	20	NITD20	125	20	20	N	
			550	25	NITD25	125	20	20	O	
			550	32	NITD32	125	20	20	O	TSA
	A2	OFFSET TAG	550	2	AAO2	100	20	20	N	
		CLOSED SLOT	550	4	AAO4	100	20	20	O	
			550	6	AAO6	100	20	20	N	
			550	10	AAO10	100	20	20	N	
			550	16	AAO16	100	20	20	N	
			550	20	AAO20	115	20	20	N	
			550	25	AAO25	115	20	20	N	
			550	32	AAO32	115	20	20	N	
	A3	OFFSET TAG	550	35	BAO35	180	20	20	N	TSS
		CLOSED SLOT	550	40	BAO40	180	20	20	N	
		(@)	550	50	BAO50	195	20	20	N	
			550	63	BAO63	210	20	20	N	TSDS
	-	OFFSET TAG	550	80	OSD80	455	20	20	N	
		CLOSED SLOT	550	100	OSD100	500	20	20	N	

Note: (@) - KO7 - Open Slot, BAO - Closed Slot
N - Normal; O - On Order

Bolted Type, 550 Volts range, Breaking Capacity - 80kA

550 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	C2	CENTRE TAG	550	450	FF450	3025	1	1	O	TST
		DOUBLE SLOT	550	500	FF500	3180	1	1	O	
			550	560	FF560	3500	1	1	O	
			550	630	FF630	3810	1	1	O	
	C3	CENTRE TAG	550	710	GF710	4060	1	1	O	TLM
		DOUBLE SLOT	550	800	GF800	4060	1	1	O	
	-	CENTRE TAG	550	710	GG710	#	1	3	O	TLT
		DOUBLE SLOT	550	800	GG800	#	1	3	O	
			550	1000	GG1000	#	1	3	O	
			550	1250	GG1250	#	1	3	O	

- Price Available on request
N - Normal; O - On Order

w.e.f from 16th March, 2026

Bolted Type, 415 Volts range, Breaking Capacity - 80kA

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	-	OFFSET TAG	550	2	EITD2	130	20	20	N	EIT
		OPEN SLOT	550	4	EITD4	130	20	20	N	
			550	6	EITD6	130	20	20	N	
			550	10	EITD10	130	20	20	N	
			550	16	EITD16	145	20	20	N	
			550	20	EITD20	145	20	20	N	
			550	25	EITD25	145	20	20	N	
			550	32	EITD32	165	20	20	N	
			415	40	EITD40	175	20	20	N	
			415	50	EITD50	185	20	20	N	
			415	63	EITD63	195	20	20	N	
	A4	OFFSET TAG	415	32	CEO32	315	10	10	O	TSD
		CLOSED SLOT	415	40	CEO40	315	10	10	O	
			415	50	CEO50	350	10	10	O	
			415	63	CEO63	350	10	10	O	
			415	80	CEO80	435	10	10	N	
			415	100	CEO100	500	10	10	N	
	-	OFFSET TAG	415	125	DEO125	455	5	5	N	TSFP
		CLOSED SLOT	415	160	DEO160	505	5	5	N	
			415	200	DEO200	560	5	5	O	
	B1	CENTRE TAG	415	80	CD80	460	10	10	O	TSDC
		SINGLE SLOT	415	100	CD100	625	10	10	N	
	B2	CENTRE TAG	415	125	DD125	545	5	5	N	TSF
		SINGLE SLOT	415	160	DD160	570	5	5	N	
			415	200	DD200	605	5	5	N	
	B3 / B4	CENTRE TAG	415	250	ED250	1195	1	1	N	TSF/TSK
		SINGLE SLOT								
	B3/B4	CENTRE TAG	415	315	ED315	1360	1	1	N	TSK
		SINGLE SLOT								
	B4	CENTRE TAG	415	355	ED355	1450	1	1	O	TSK/TSM
		SINGLE SLOT	415	400	ED400	1470	1	1	N	

N - Normal; O - On Order

Bolted Type, 415 Volts range, Breaking Capacity - 80kA

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	-	CENTRE TAG	415	355	355SN11(S)	#	1	1	O	TSMs
		SINGLE SLOT	415	400	400SN11(S)	1695	1	1	N	
	-	CENTRE TAG	415	450	450SP11(S)	2070	1	1	O	TSTS
		SINGLE SLOT	415	500	500SP11(S)	2385	1	1	O	
	-	CENTRE TAG	415	560	560SR11(S)	3180	1	1	O	TSLs
		SINGLE SLOT	415	630	630SR11(S)	3650	1	1	N	
			415	710	710SR11(S)	#	1	1	O	
			415	800	800SR11(S)	4060	1	1	N	
	C1	CENTRE TAG	415	355	EF355	#	1	1	O	TSM
		DOUBLE SLOT	415	400	EF400	2790	1	1	O	
	-	CENTRE TAG	415	710	710SR11	#	1	1	O	TSL
		DOUBLE SLOT	415	800	800SR11	5065	1	1	N	

N - Normal; O - On Order

w.e.f from 16th March, 2026

Low Voltage DIN Type, NH Dual Indicator Fuse Links

Rated Voltage 500 Volts AC, Breaking Capacity - 120 kA

500 Vac	Size	Rated Current (A)	Class gL-gG with Dual Indication & Metal Grips	MRP (₹)	Carton Qty.	MOQ	Delivery Class
 	000	2	2NHG000B	480	3	3	N
		4	4NHG000B	480	3	3	N
		6	6NHG000B	480	3	3	N
		10	10NHG000B	480	3	3	N
		16	16NHG000B	480	3	3	N
		20	20NHG000B	500	3	3	N
		25	25NHG000B	500	3	3	N
		32	32NHG000B	500	3	3	N
		35	35NHG000B	500	3	3	O
		40	40NHG000B	550	3	3	N
	00	50	50NHG000B	550	3	3	N
		63	63NHG000B	550	3	3	N
		80	80NHG000B	565	3	3	N
		100	100NHG000B	585	3	3	N
		63	63NHG00B	580	3	3	N
	00	80	80NHG00B	625	3	3	N
		100	100NHG00B	625	3	3	N
		125	125NHG00B	625	3	3	N
		160	160NHG00B	655	3	3	O
	0®	50	50NHG0B	770	3	3	O
		63	63NHG0B	770	3	3	O
		80	80NHG0B	850	3	3	O
		100	100NHG0B	850	3	3	O
	0s	125	125NHG0B	850	3	3	O
		160	160NHG0B	860	3	3	O
 	01®	200	200NHG0SB	895	3	3	O
		100	100NHG01B	890	3	3	O
		125	125NHG01B	890	3	3	O
		160	160NHG01B	920	3	3	O
	1	200	200NHG1B	960	3	3	N
		224	224NHG1B	960	3	3	O
		250	250NHG1B	1015	3	3	N
		315#	315NHG1B#	1255	3	3	O
		355	355NHG1B	1285	3	3	O
	02	35	35NHG02B	940	3	3	O
		40	40NHG02B	#	3	3	O
		50	50NHG02B	#	3	3	O
		63	63NHG02B	#	3	3	O
		80	80NHG02B	#	3	3	O
		100	100NHG02B	1035	3	3	O
		125	125NHG02B	1065	3	3	O
		160	160NHG02B	1080	3	3	O
		200	200NHG02B	1095	3	3	O
		224	224NHG02B	1095	3	3	O
		250	250NHG02B	1125	3	3	O
	2	315	315NHG2B	1335	3	3	N
		355	355NHG2B	1355	3	3	O
		400	400NHG2B	1370	3	3	N
	03	250	250NHG03B	1795	3	3	O
		315	315NHG03B	1825	3	3	O
		355	355NHG03B	1850	3	3	O
		400	400NHG03B	1930	3	3	O
 	3	425	425NHG3B	1960	3	3	O
		450	450NHG3B	1960	3	3	O
		500	500NHG3B	2135	3	3	N
		630	630NHG3B	2265	3	3	N
		800*#	800NHG3B*#	3015	3	3	N

@ Size "0", 6A - 63A on request
Size "1" 80A-160A on request
Insulated grip version available on request
800VAC gG fuse available on request

Size "01", 6A - 80A on request
Rated Voltage 440V
500/ 630/ 800/ 1000/ 1250 Amp | 500 V | Size 4 available on request

* Available in Single Indicator type only

N - Normal; O - On Order
- Price Available on request

w.e.f from 16th March, 2026

HRC High Speed Fuses - Semi Conductor Protection Fuses - BS88 Type

Rated Voltage 240 V AC/ 150 V DC, Breaking Capacity - 200 kA

240 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	240	6	6LCT	265	20	20	N
	240	10	10LCT	265	20	20	N
	240	12	12LCT	265	20	20	O
	240	16	16LCT	265	20	20	N
	240	20	20LCT	265	20	20	N
	240	25	25LET	475	10	10	N
	240	32	32LET	500	10	10	N
	240	35	35LET	500	10	10	O
	240	50	50LET	525	10	10	N
	240	63	63LET	525	10	10	N
	240	80	80LET	550	10	10	N
	240	100	100LET	550	10	10	O
	240	125	125LET	585	10	10	N
	240	160	160LET	605	10	10	N
	240	180	180LET	645	10	10	N
	240	160	160LMT	965	1	1	N
	240	200	200LMT	1020	1	1	N
	240	250	250LMT	1245	1	1	N
	240	315	315LMT	1755	1	1	N
	240	355	355LMT	1865	1	1	N
	240	400	400LMT	1975	1	1	N
	240	450	450LMT	2260	1	1	N
	240	400	400LMMT	2625	1	1	O
	240	500	500LMMT	2850	1	1	O
	240	630	630LMMT	3130	1	1	O
	240	710	710LMMT	3310	1	1	O
	240	800	800LMMT	3940	1	1	O
	240	900	900LMMT	4400	1	1	O

N - Normal; O - On Order

Rated Voltage 690 Volts AC/ 500VDC, Breaking Capacity - 200 kA

690 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	690	6	6CT	270	20	20	N
	690	10	10CT	270	20	20	N
	690	12	12CT	270	20	20	O
	690	16	16CT	290	20	20	N
	690	20	20CT	290	20	20	N
	690	15	15ET	580	10	10	N
	690	25	25ET	580	10	10	N
	690	32	32ET	580	10	10	N
	690	35	35ET	580	10	10	N
	690	40	40ET	580	10	10	N
	690	45	45ET	580	10	10	N
	690	56	56ET	645	10	10	N
	690	63	63ET	645	10	10	N
	690	80	80ET	710	10	10	N

N - Normal; O - On Order

w.e.f from 16th March, 2026

HRC High Speed Fuses - Semi Conductor Protection Fuses - BS88 Type

Rated Voltage 690 Volts AC / 500 Volts DC, Breaking Capacity - 200 kA

690 Vac	Voltage (V)	Rating (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	690	35	35FE	615	10	10	N
	690	40	40FE	615	10	10	O
	690	45	45FE	615	10	10	N
	690	50	50FE	615	10	10	N
	690	63	63FE	695	10	10	N
	690	71	71FE	715	10	10	O
	690	80	80FE	765	10	10	N
	690	90	90FE	910	10	10	N
	690	100	100FE	910	10	10	N
	690	75	75EET	1380	5	5	O
	690	90	90EET	1380	5	5	N
	690	110	110EET	1380	5	5	N
	690	140	140EET	1410	5	5	N
	690	160	160EET	1410	5	5	N
	690	100	100FEE	1440	5	5	N
	690	120	120FEE	1505	5	5	N
	690	140	140FEE	1560	5	5	N
	690	160	160FEE	1585	5	5	N
	690	180	180FEE	1625	5	5	O
	690	200	200FEE	1665	5	5	N
	690	160	160MT	1290	1	1	N
	690	180	180MT	1340	1	1	N
	690	200	200MT	1690	1	1	N
	690	250	250MT	#	1	1	N
	690	280	280MT	#	1	1	N
	690	315	315MT	2420	1	1	N
	690	355	355MT	2465	1	1	N
	690	180	180MMT	2400	1	1	N
	690	200	200MMT	2515	1	1	N
	690	225	225MMT	2595	1	1	N
	690	280	280MMT	2660	1	1	N
	690	315	315MMT	2655	1	1	N
	690	355	355MMT	3070	1	1	N
	690	400	400MMT	3185	1	1	N
	690	450	450MMT	3580	1	1	N
	690	500	500MMT	3970	1	1	N
	690	560	560MMT	4720	1	1	N
	690	630	630MMT	4895	1	1	N
	690	710	710MMT	5265	1	1	N
	690	180	180FM	1340	1	1	O
	690	200	200FM	1520	1	1	N
	690	225	225FM	1580	1	1	N
	690	250	250FM	1605	1	1	N
	690	280	280FM	1800	1	1	O
	690	315	315FM	2460	1	1	N
	690	350	350FM	2555	1	1	N
	690	400	400FMM	2735	1	1	N
	690	450	450FMM	2860	1	1	N
	690	500	500FMM	3225	1	1	N
	690	550	550FMM	3435	1	1	N
	690	630	630FMM	4020	1	1	N
	690	700	700FMM	4430	1	1	N

N - Normal; O - On Order
- Price Available on request

w.e.f from 16th March, 2026

Accessories

	Catalogue No. / Type	Trip Indicator accessory pack (each consists of 1 pair of clip & appropriate size Trip Indicator Fuse Link)	MRP (₹)	Pack Quantity	Delivery Class
	EC-250	For use with LET	1195	1 set	O
	EC-600	For use with ET, EET, FE & FEE	1280	1 set	O
	MC-250	For use with LMT & LMMT	1195	1 set	O
	MC-600	For use with FM & FMM	1280	1 set	O
	MC-700	For use with MT & MMT	1340	1 set	O

	Catalogue No. / Type	Micro - Switch	MRP (₹)	Pack Quantity	Delivery Class
	MAI	Micro-switch & Adapter assly.	1555	1	O
	MBI	Micro-switch & Adapter assly.	#	1	O

- Price Available on request

	Catalogue No. / Type	Fuse Clips for Fitting Trip Indicator	MRP (₹)	Pack Quantity	Delivery Class
	ECLIP	For use with LET, ET, EET, FE & FEE	205	10	O
	MCLIP	For use with LMT, LMMT, MT, MMT, FM & FMM	445	10	O
	CL1	Back connected Clip for use with Trip Indicator fuse	1495	1 set	O

	Catalogue No. / Type	Trip Indicators for Fuse Links	MRP (₹)	Pack Quantity	Delivery Class
	TI250-BT	For use with LET, LMT & LMMT	1225	10	O
	TI500-BT	For use with ET, EET, FE & FEE, FM & FMM	1255	1	O
	TI600-BT	For use with ET, EET, FE & FEE, FM & FMM	#	1	O
	TI700-BT	For use with MT & MMT	1565	1	O
	TI1100-BT	For replacement only	1740	1	O
	TI1500-BT	For replacement only	1800	1	O
	TI2000-BT	For replacement only	#	1	O

- Price Available on request
N - Normal; O - On Order

NH Fuse base

	Catalogue No. / Type	Fuse Accessories	MRP (₹)	Pack Quantity	Delivery Class
	SD1-S	NH Fuse base 250A, 690VAC DIN Size 1 (Screw Mounting)	1135	3	O
	SD2-S	NH Fuse base 400A, 690VAC DIN Size 2 (Screw Mounting)	1675	3	O
	SD3-S	NH Fuse base 630A, 690VAC DIN Size 3 (Screw Mounting)	2430	3	O
	SD4-S	NH Fuse base 1250A, 690VAC DIN Size 4 (Screw Mounting)	6050	1	O

N - Normal; O - On Order

w.e.f from 16th March, 2026

British Standard Type Range of Fuses for use in Air

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	Air (Bus Duct / Distribution)	3.3 / 3.6	25	15	3.6ADGHC15	4855	1	1	O
		3.3 / 3.6	25	20	3.6ADGHC20	4855	1	1	O
		3.3 / 3.6	25	25	3.6ADGHC25	4855	1	1	O
		3.3 / 3.6	25	30	3.6ADGHC30	4855	1	1	O
		3.3 / 3.6	25	40	3.6ADGHC40	4855	1	1	O
		3.3 / 3.6	25	45	3.6ADGHC45	5300	1	1	O
		3.3 / 3.6	25	50	3.6ADGHC50	5385	1	1	O
		3.3 / 3.6	25	60	3.6ADGHC60	5740	1	1	O
		3.3 / 3.6	25	70	3.6ADGHC70	5740	1	1	O
		3.3 / 3.6	25	75	3.6ADGHC75	#	1	1	O
		3.3 / 3.6	25	80	3.6ADGHC80	6355	1	1	O
	Air (Bus Duct / Distribution)	3.3 / 3.6	25	90	3.6ADGHC90	6480	1	1	O
		3.3 / 3.6	25	100	3.6ADGHC100	6480	1	1	O
		6.6 / 7.2	40	10	7.2BDGHC10	4910	1	1	O
		6.6 / 7.2	40	16	7.2BDGHC16	4910	1	1	O
		6.6 / 7.2	40	20	7.2BDGHC20	4910	1	1	O
		6.6 / 7.2	40	25	7.2BDGHC25	4910	1	1	O
		6.6 / 7.2	40	31.5	7.2BDGHC31.5	4910	1	1	O
		6.6 / 7.2	40	35.5	7.2BDGHC35.5	4910	1	1	O
		6.6 / 7.2	40	40	7.2BDGHC40	4910	1	1	O
		6.6 / 7.2	40	45	7.2BDGHC45	#	1	1	O
		6.6 / 7.2	40	50	7.2BDGHC50	5000	1	1	O
	Air (Bus Duct / Distribution)	6.6 / 7.2	40	56	7.2BDGHC56	5000	1	1	O
		6.6 / 7.2	40	60	7.2BDGHC60	5000	1	1	O
		6.6 / 7.2	40	63	7.2BDGHC63	5325	1	1	O
		6.6 / 7.2	40	71	7.2BDGHC71	6330	1	1	O
		6.6 / 7.2	40	80	7.2BDGHC80	6625	1	1	O
		6.6 / 7.2	40	50	7.2AHGHC50	#	1	1	O
		6.6 / 7.2	40	60	7.2AHGHC60	6225	1	1	O
		6.6 / 7.2	40	75	7.2AHGHC75	6565	1	1	O
		6.6 / 7.2	40	90	7.2AHGHC90	6935	1	1	O
		6.6 / 7.2	40	100	7.2AHGHC100	7155	1	1	O
		6.6 / 7.2	40	112	7.2AHGHC112	#	1	1	O
		6.6 / 7.2	40	125	7.2AHGHC125	8400	1	1	O
		6.6 / 7.2	40	140	7.2AHGHC140	9160	1	1	O
		6.6 / 7.2	40	150	7.2AHGHC150	9160	1	1	O
		6.6 / 7.2	40	160	7.2AHGHC160	9425	1	1	N
		6.6 / 7.2	40	160	7.2AHGNB160 (NS)	8775	1	1	O
		6.6 / 7.2	40	50	7.2AHGHB50	5920	1	1	O
		6.6 / 7.2	40	60	7.2AHGHB60	5920	1	1	O
		6.6 / 7.2	40	65	7.2AHGHB65	6230	1	1	O
		6.6 / 7.2	40	75	7.2AHGHB75	6875	1	1	O
		6.6 / 7.2	40	90	7.2AHGHB90	6895	1	1	N
		6.6 / 7.2	40	100	7.2AHGHB100	6925	1	1	O
		6.6 / 7.2	40	112	7.2AHGHB112	8045	1	1	O
		6.6 / 7.2	40	120	7.2AHGHB120	8365	1	1	O
		6.6 / 7.2	40	125	7.2AHGHB125	8585	1	1	O
		6.6 / 7.2	40	140	7.2AHGHB140	9135	1	1	O
6.6 / 7.2	40	150	7.2AHGHB150	9135	1	1	O		
	6.6 / 7.2	40	160	7.2AHGHB160	9535	1	1	O	
	6.6 / 7.2	20	30	7.2AEFMO 30	#	1	1	O	
	6.6 / 7.2	20	35	7.2AEFMO 35	6155	1	1	O	
	6.6 / 7.2	20	40	7.2AEFMO 40	6155	1	1	O	
	6.6 / 7.2	20	50	7.2AEFMO 50	#	1	1	O	
	6.6 / 7.2	20	56	7.2AEFMO 56	6785	1	1	O	
	6.6 / 7.2	20	63	7.2AEFMO 63	6785	1	1	O	
	6.6 / 7.2	20	71	7.2AEFMO 71	#	1	1	O	
	6.6 / 7.2	20	80	7.2AEFMO 80	7100	1	1	O	
6.6 / 7.2	20	90	7.2AEFMO 90	7540	1	1	O		

- Price Available on request
(NS) Non striker

N - Normal; O - On Order

For ordering HV Air Fuse with Single Slot

- 1 - For BD _____ series, add "S" at the end of the cat. number. For ex : For ordering 100A, 7.2BFGHD catalogue no. will be "7.2BFGHD100S"
- 2 - For AH _____ series, replace "C" at end with "B" For ex : For ordering 100A, 7.2AHGH series, catalogue no. will be "7.2AHGHB100"
- 3 - For "7.2BFGHD" ___ series, completely replaced with "7.2AHGHB".

w.e.f from 16th March, 2026

British Standard Type Range of Fuses for use in Air

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	Air (Bus Duct/ Distribution)	11 / 12	40	6.3	12BDGHC6.3	5780	1	1	O
		11 / 12	40	10	12BDGHC10	5780	1	1	O
		11 / 12	40	16	12BDGHC16	5780	1	1	O
		11 / 12	40	20	12BDGHC20	5780	1	1	O
		11 / 12	40	25	12BDGHC25	5285	1	1	N
		11 / 12	40	31.5	12BDGHC31.5	5325	1	1	O
		11 / 12	40	35.5	12BDGHC35.5	5325	1	1	O
		11 / 12	40	40	12BDGHC40	5405	1	1	O
		11 / 12	40	45	12BDGHC45	5405	1	1	O
		11 / 12	40	50	12BDGHC50	5500	1	1	O
		11 / 12	40	56	12AHGHC56	#	1	1	O
		11 / 12	40	63	12AHGHC63	6240	1	1	N
		11 / 12	40	70	12AHGHC70	6260	1	1	O
		11 / 12	40	80	12AHGHC80	6715	1	1	N
		11 / 12	40	90	12AHGHC90	6725	1	1	O
		11 / 12	40	100	12AHGHC100	6840	1	1	O
		11 / 12	40	56	12AHGHB56	6215	1	1	O
		11 / 12	40	63	12AHGHB63	6265	1	1	N
		11 / 12	40	65	12AHGHB65	6525	1	1	O
		11 / 12	40	70	12AHGHB70	6525	1	1	N
		11 / 12	40	80	12AHGHB80	6825	1	1	O
		11 / 12	40	90	12AHGHB90	6965	1	1	O
		11 / 12	40	100	12AHGHB100	7090	1	1	N
		11 / 12	40	112	12AKGHD 112	18670	3	3	O
		11 / 12	40	125	12AKGHD 125	15905	1	1	O
		11 / 12	20	3.7	12AEFMO 3.7	6205	1	1	O
		11 / 12	20	12	12AEFMO 12	#	1	1	O
		11 / 12	20	15	12AEFMO 15	6140	1	1	O
		11 / 12	20	16.8	12AEFMO 16.8	6140	1	1	O
		11 / 12	20	22	12AEFMO 22	6175	1	1	O
		11 / 12	20	26.6	12AEFMO 26.6	#	1	1	O
		11 / 12	20	30	12AEFMO 30	6175	1	1	O
		11/12	20	33.75	12AEFMO 33.75	6345	1	1	O
		11 / 12	20	37.5	12AEFMO 37.5	6345	1	1	O
		11 / 12	20	42	12AEFMO 42	6235	1	1	O
		11 / 12	20	47.25	12AEFMO 47.25	6235	1	1	O

- Price Available on request

N - Normal; O - On Order

For ordering HV Air Fuse with Single Slot -

1 - For "12BFGHD"___ series, completely replaced with "12AHGHB".

w.e.f from 16th March, 2026

For use in Oil

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	Oil	6.6 / 7.2	45	100	7.2OEFMA100	#	1	1	O
	Oil	11 / 12	40	6.3	12OEFMA6.3	#	3	3	O
		11 / 12	40	10	12OEFMA10	6750	3	3	O
		11 / 12	40	16	12OEFMA16	6750	3	3	O
		11 / 12	40	20	12OEFMA20	6765	3	3	O
		11 / 12	40	25	12OEFMA25	6765	3	3	O
		11 / 12	40	31.5	12OEFMA31.5	6765	3	3	O
		11 / 12	40	40	12OEFMA40	6780	3	3	O
		11 / 12	40	50	12OEFMA50	6780	3	3	O
		11 / 12	40	63	12OEFMA63	6780	3	3	O
11 / 12		40	71	12OHFMA71	7015	3	3	O	
11 / 12		40	80	12OHFMA80	7015	3	3	O	
11 / 12		40	16	12OHGMA16	#	3	3	O	
11 / 12		40	25	12OHGMA25	8285	3	3	O	
11 / 12		40	31.5	12OHGMA31.5	8285	3	3	O	
11 / 12		40	40	12OHGMA40	8325	3	3	O	
11 / 12		40	50	12OHGMA50	8325	3	3	O	
11 / 12		40	63	12OHGMA63	8325	3	3	O	
11 / 12		40	80	12OHGMA80	8325	3	3	O	
11 / 12		40	90	12OHGMA90	8640	3	3	O	
11 / 12		40	100	12OHGMA100	9445	3	3	O	
11 / 12		40	125	12OLGMA125	10615	3	3	O	

N - Normal; O - On Order

For use in PT / VT & Auxiliary Transformer

	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNA3.15	1220	1	1	N
		3.3 / 3.6	50	6.3	3.6ABWNA6.3	1220	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNA3.15	1335	1	1	N
		6.6 / 7.2	45	6.3	7.2ABCNA6.3	#	1	1	O
		6.6 / 7.2	45	3.15	7.2ABWNA3.15	1320	1	1	O
		6.6 / 7.2	45	6.3	7.2ABWNA6.3	1320	1	1	O
		11 / 12	45	3.15	12ABCNA3.15	1350	1	1	N
		22 / 24	25	3.15	24ABGNA3.15	3090	1	1	N
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNS3.15	#	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNS3.15	1440	1	1	O
		11 / 12	45	3.15	12ABCNS3.15	1570	1	1	O
	VT / PT	3.3 / 3.6	50	3.15	3.6ABWNT3.15	1495	1	1	O
		6.6 / 7.2	45	3.15	7.2ABCNT3.15	#	1	1	O
		11 / 12	45	3.15	12ABCNT3.15	#	1	1	O

N - Normal; O - On Order
1A PT fuse available on request
- Price Available on request

w.e.f from 16th March, 2026

British Standard Type Range of Fuses for use in Motor Circuits


	Application (used in)	Voltage (Kv)	Breaking Capacity (kA)	Ratings (Amps)	Catalogue No. / Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	For use in MV Motor Circuits	3.6	50	5	3.6WDOHS5	#	1	1	O
		3.6	50	16	3.6WDOHS16	5195	1	1	O
		3.6	50	20	3.6WDOHS20	5290	1	1	N
		3.6	50	25	3.6WDOHS25	#	1	1	O
		3.6	50	32	3.6WDOHS32	5390	1	1	N
		3.6	50	40	3.6WDOHS40	5585	1	1	O
		3.6	50	50	3.6WDOHS50	#	1	1	O
		3.6	50	63	3.6WDOHS63	5635	1	1	N
		3.6	50	80	3.6WDOHS80	5685	1	1	O
		3.6	50	50	3.6WDFMO50	#	1	1	O
		3.6	50	63	3.6WDFMO63	#	1	1	O
		3.6	50	80	3.6WDFMO80	7585	1	1	O
		3.6	50	100	3.6WDFMO100	8015	1	1	O
		3.6	50	100	3.6WFFMO100	9865	1	1	O
		3.6	50	140	3.6WFFMO140	11000	1	1	O
		3.6	50	160	3.6WFFMO160	11310	1	1	O
		3.6	50	200	3.6WFFMO200	12255	1	1	N
		3.6	50	250	3.6WFFMO250	13890	1	1	O
		3.6	50	315	3.6WFFMO315	16045	1	1	O
		3.6	50	350	3.6WFFMO350	17755	1	1	O
		3.6	50	450	3.6WFFMO450	26695	1	1	O
		3.6	50	630	3.6WKFM0630	34220	1	1	O
	For use in MV Motor Circuits	7.2	45	50	7.2WFNMO50	10485	1	1	O
		7.2	45	63	7.2WFNMO63	11185	1	1	O
		7.2	45	80	7.2WFNMO80	12740	1	1	O
		7.2	45	100	7.2WFNMO100	13330	1	1	O
		7.2	45	125	7.2WFNMO125	14725	1	1	O
		7.2	45	160	7.2WFNMO160	15140	1	1	O
		7.2	45	200	7.2WFNMO200	17330	1	1	O
		7.2	45	250	7.2WFNMO250	20495	1	1	O
		7.2	45	50	7.2WFQMO50	11970	1	1	N
		7.2	45	63	7.2WFQMO63	12085	1	1	N
		7.2	45	80	7.2WFQMO80	13380	1	1	N
		7.2	45	100	7.2WFQMO100	14205	1	1	N
		7.2	45	125	7.2WFQMO125	16570	1	1	N
		7.2	45	160	7.2WFQMO160	17480	1	1	O
		7.2	45	200	7.2WFQMO200	18860	1	1	O
		7.2	45	250	7.2WFQMO250	23365	1	1	O
		7.2	45	350	7.2WKQMO350	31555	1	1	O
		7.2	45	400	7.2WKQMO400	53165	1	1	O

N - Normal; O - On Order
- Price Available on request

w.e.f from 16th March, 2026

BS Fuse link Type SS/NS/ES


Clip-on Fuse links with Staggered Tags-415 V AC

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	E1	SMALL CLIP ON	415	2	SS2	#	20	20	O	SSD
		TAG	415	4	SS4	105	20	20	N	
			415	6	SS6	105	20	20	N	
			415	10	SS10	#	20	20	O	
			415	16	SS16	110	20	20	O	
			415	20	SS20	110	20	20	O	
	F1	CLIP ON	415	2	NS2	155	20	20	N	NSD
		TAG	415	4	NS4	155	20	20	N	
			415	6	NS6	155	20	20	N	
			415	10	NS10	155	20	20	N	
			415	16	NS16	155	20	20	N	
			415	20	NS20	185	20	20	N	
			415	25	NS25	185	20	20	N	
			415	32	NS32	185	20	20	N	
	F2	LONG CLIP ON	415	2	ES2	#	20	20	O	ESD
		TAG	415	4	ES4	150	20	20	O	
			415	6	ES6	150	20	20	O	
			415	10	ES10	#	20	20	O	
			415	16	ES16	150	20	20	O	
			415	20	ES20	#	20	20	O	
			415	25	ES25	#	20	20	O	
			415	32	ES32	#	20	20	O	
			415	36	ES36	#	20	20	O	
			415	50	ES50	215	20	20	N	
			415	63	ES63	220	20	20	N	

N - Normal; O - On Order

BS Fuse link Type EIT

Fuse link with Offset Tags



415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
		OFFSET TAG	415	2	EIT2	175	20	20	O	EITD
		OPEN SLOT	415	4	EIT4	175	20	20	O	
			415	6	EIT6	175	20	20	N	
			415	10	EIT10	175	20	20	N	
			415	16	EIT16	175	20	20	N	
			415	20	EIT20	180	20	20	N	
			415	25	EIT25	180	20	20	N	
			415	32	EIT32	180	20	20	N	
			415	36	EIT36	215	20	20	O	
			415	50	EIT50	215	20	20	O	
			415	63	EIT63	220	20	20	N	

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order
- Price Available on request

w.e.f from 16th March, 2026


Fuse link with Offset Tags Closed Slot

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	A2	OFFSET TAG	415	6	TSA6	185	20	20	O	AAO
		CLOSED SLOT	415	10	TSA10	185	20	20	O	
			415	16	TSA16	185	20	20	N	
			415	20	TSA20	185	20	20	O	
			415	25	TSA25	185	20	20	N	
			415	32	TSA32	185	20	20	N	
	A3	OFFSET TAG	415	36	TSS36	220	20	20	N	BAO
		CLOSED SLOT	415	50	TSS50	385	20	20	N	
			415	63	TSS63	385	20	20	N	
	-	OFFSET TAG	415	80	TSDS80	550	10	10	N	OSD
		CLOSED SLOT	415	100	TSDS100	550	10	10	N	
			415	125	TSDS125	550	10	10	N	
	A4		415	125	TSD125	900	10	10	N	CEO
	-	OFFSET TAG	415	125	TSFP125	900	10	10	O	DEO
		CLOSED SLOT	415	160	TSFP160	900	10	10	N	
			415	200	TSFP200	900	10	10	O	

N - Normal; O - On Order

Type - TSDC \ TSK \ TSMS \ TSTS \ TSLs

Fuse Links with Centre Tag Single Slot

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B3	Centre Tag	415	250	TSK250	1690	10	10	N	ED
		Single Slot	415	315	TSK315	1690	10	10	N	
	-	Centre Tag	415	450	TSTS450	2770	1	1	O	SN11(S)
		Single Slot	415	500	TSTS500	#	1	1	O	SP11(S)
	-	Centre Tag	415	560	TSLs560	#	1	1	O	
		Single Slot	415	630	TSLs630	4165	1	1	O	SR11(S)
			415	710	TSLs710	4165	1	1	O	
			415	750	TSLs750	4185	1	1	O	
			415	800	TSLs800	#	1	1	N	


Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

- Price Available on request

w.e.f from 16th March, 2026


Fuse link with Offset Tags Double Slot

415 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	C1	Centre Tag	415	355	TSM355	2965	1	1	O	EF
		Double Slot	415	400	TSM400	#	1	1	O	
	C2	Centre Tag	415	450	TST450	2450	1	1	O	FF
		Double Slot	415	500	TST500	#	1	1	O	
	C3	Centre Tag	415	560	TSL560	4470	1	1	O	SR11
		Double Slot	415	630	TSL630	4610	1	1	N	
			415	710	TSL710	4610	1	1	O	
			415	750	TSL750	4615	1	1	O	
			415	800	TSL800	4885	1	1	N	

N - Normal; O - On Order

Type - TM \ TTM \ TLM


Fuse Links with Centre Tags Double Slot

660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	C1	Centre Tag	660	355	TM355	2790	1	1	O	SP11
		Double Slot	660	400	TM400	2890	1	1	O	
	C2	Centre Tag	660	450	TTM450	3250	1	1	O	R11
		Double Slot	660	500	TTM500	3385	1	1	O	
			660	560	TTM560	3795	1	1	O	
			660	630	TTM630	3955	1	1	O	
	C3	Centre Tag	660	630	TLM630	#	1	1	O	GF
		Double Slot	660	710	TLM710	7045	1	1	O	
			660	750 & 800	TLM750 & 800	#	1	1	O	

N - Normal; O - On Order

Type TIA \ TIS \ TCP \ TFP

Fuse with Offset Tags (2 hole fixing - Bolted)


660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	A2	OFFSET TAG	660	2	TIA2	185	10	10	O	HO7
		CLOSED SLOT	660	4	TIA4	185	10	10	O	
			660	6	TIA6	225	10	10	N	
			660	10	TIA10	225	10	10	N	
			660	16	TIA16	225	10	10	N	
			660	20	TIA20	225	10	10	N	
			660	25	TIA25	225	10	10	N	
			660	32	TIA32	225	10	10	N	
	A3	OFFSET TAG	660	36	TIS36	295	10	10	N	KO7
		CLOSED SLOT	660	40	TIS40	325	10	10	O	
			660	50	TIS50	325	10	10	N	
			660	63	TIS63	325	10	10	N	
	A4	OFFSET TAG	660	80	TCP80	905	6	6	N	L14
		CLOSED SLOT	660	100	TCP100	905	6	6	N	
			660	125	TFP125	1430	3	3	O	M14
			660	160	TFP160	1430	3	3	O	
			660	200	TFP200	1430	3	3	O	

- Price Available on request

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

w.e.f from 16th March, 2026

Fuse with Central Tags

660 Vac	BS Size	Tag Type	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class	
	B1	CENTRE TAG	660	80	TC80	965	6	6	O	LO9
		SINGLE SLOT	660	100	TC100	965	6	6	N	
			660	80	102TC80	605	6	6	O	
			660	100	102TC100	675	6	6	O	
	B3	CENTRE TAG	660	250	TKF250	2155	1	1	N	NO9
		SINGLE SLOT	660	315	TKF315	2155	1	1	N	

N - Normal; O - On Order

Moulded Fuse Holder and Fuse Base for 415V AC Circuit

Type - SC (Safe Clip)

IS / BS Size Reference	Description	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
E1	-	Front	SS	20	SC20H	415	#	10	10	O
F1	-	Front	NS	32	SC32H	415	#	10	10	O

N - Normal; O - On Order

Fuse Fittings for LV BS Type of Fuses

Type - NS & SM: Moulded Fuse Holder

IS / BS Size Reference	Description	Connection Type	Suitable for Fuse Type	Rating (Amps)	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Carton Qty.	MOQ	Delivery Class
F1		Front	NS (upto 32A)	32	NSH32	415	380	10	10	N
		Back	NS (upto 32A)	32	NSP32	415	0	10	10	N
		Busbar	NS (upto 32A)	32	NSB32	415	0	10	10	N
A2	Offset Bolted	Front	TIA / TSA	32	SM32H	660	560	10	10	N
		Busbar	TIA / TSA	32	SM32B	660	710	10	10	N
A3	Offset Bolted	Front	TIA / TSS	63	SM63H	660	730	10	10	N
		Busbar	TIA / TSS	63	SM63B	660	820	10	10	N
A4	Offset Bolted	Front	TCP / TSD	125	SM125H	660	1845	5	10	N
		Busbar	TCP / TSD	125	SM125B	660	2030	5	10	N

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order

Type GSMJ/GSMK/SMK Ultra-fast Acting Multi Body Fuselink for

Fuselink for Diode & Thyristor Protection

800 \ 1000 Vac	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	800	63	GSMJ63	1440	3	3	O
	800	120	GSMJ120	3345	1	1	O
	800	180	GSMJ180	#	2	2	O
	800	240	GSMJ240	6545	1	1	O
	800	300	GSMJ300	#	1	1	O
	800	350	GSMJ350	9850	1	1	O
	800	400	GSMJ400	11560	1	1	O
	800	460	GSMJ460	#	1	1	O
	800	520	GSMJ520	14060	1	1	O
	800	580	GSMJ580	#	1	1	O
	800	630	GSMJ630	18850	1	1	O
	800	680	GSMJ680	20835	1	1	O
	800	800	GSMJ800	#	1	1	O
	800	1000	GSMJ1000	33570	1	1	O
	800	1200	GSMJ1200	38270	1	1	O
	1000	63	GSMK63	730	3	3	O
	1000	120	GSMK120	3510	2	2	O
	1000	180	GSMK180	5140	2	2	O
	1000	240	GSMK240	7350	1	1	O
	1000	300	GSMK300	#	2	2	O
	1000	350	GSMK350	10430	2	2	O
	1000	400	GSMK400	#	1	1	O
	1000	460	GSMK460	#	1	1	O
	1000	520	GSMK520	16995	1	1	O
	1000	580	GSMK580	18270	1	1	O
	1000	630	GSMK630	20425	1	1	O
	1000	680	GSMK680	22425	1	1	O
	1000	800	GSMK800	#	1	1	O
	1000	1000	GSMK1000	#	1	1	O
	1000	1200	GSMK1200	43405	1	1	O
	-	2000	SMK-GSM120-1200	710	1	1	O
	-	400	954GSMJ400	#	1	1	O
	1000	500	RG5500	10625	1	1	O

N - Normal; O - On Order

Trip Indicator Fuse

	Cat. No. / Type	Rated Voltage (Volts)	MRP (₹)	Pack Qty.	MOQ	Delivery Class
	TI300-BI	300	825	20	20	N
	TI600-BI	600	870	20	20	N
	TI1200-BI	1200	885	20	20	N
	TI2000-BI	2000	995	20	20	N

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order
- Price Available on request

w.e.f from 16th March, 2026

British Standard Type Range of Fuses for use in Motor Circuits

3.6 / 7.2 KV	Rated Voltage (Volts)	Rating (Amps)	Cat. No./ Type	MRP (₹)	Carton Qty.	MOQ	Delivery Class
	3.6	5	K3PGX5	#	1	1	O
	3.6	10	K3PGX10	#	1	1	O
	3.6	16	K3PGX16	7830	1	1	O
	3.6	20	K3PGX20	#	1	1	O
	3.6	25	K3PGX25	7830	1	1	O
	3.6	32	K3PGX32	7830	1	1	O
	3.6	40	K3PGX40	7830	1	1	O
	3.6	50	K3PGX50	7985	1	1	O
	3.6	63	K3PGX63	8005	1	1	O
	3.6	80	K3PGX80	#	1	1	O
	3.6	100	K81PEX100	13625	1	1	O
	3.6	160	K81PEX160	15290	1	1	N
	3.6	200	K81PEX200	17245	1	1	O
	3.6	250	K81PEX250	19790	1	1	N
	3.6	315	K81PEX315	23925	1	1	O
	3.6	350	K81PEX350	#	1	1	N
	7.2	50	K81SVX50	16900	1	1	O
	7.2	63	K81SVX63	17060	1	1	N
	7.2	80	K81SVX80	18590	1	1	N
	7.2	100	K81SVX100	21365	1	1	N
	7.2	125	K81SVX125	23480	1	1	N
	7.2	160	K81SVX160	23920	1	1	O
	7.2	200	K81SVX200	27925	1	1	O
	7.2	250	K81SVX250	34295	1	1	O
	7.2	50	KSVX50	#	1	1	O
	7.2	63	KSVX63	#	1	1	O
	7.2	80	KSVX80	18225	1	1	O
	7.2	100	KSVX100	#	1	1	O
	7.2	125	KSVX125	18555	1	1	O
	7.2	160	KSVX160	21000	1	1	O
	7.2	200	KSVX200	23925	1	1	O
	7.2	250	KSVX250	27345	1	1	O

Note: Please discuss with Eaton sales team before placing any orders for these set of products.

N - Normal; O - On Order
- Price Available on request

w.e.f from 16th March, 2026

Cross Reference Chart

LV BUS FUSES

Clip on Type

BS Size	Bussmann	Bussmann
E1	SSD	SS
F1	NSD	NS
F2	ESD	ES

Bolted Type - 550V Range

BS Size	Bussmann	Bussmann*
A1	NITD	NIT
A2	AAO	TSA
A3	BAO*	TSS
A4	CEO	TSD
-	OSD	TSDS
C2	FF	TST
C3	GF	TLM
-	GG	TLT

*Fuses are 415V rated

Bolted Type - 660V Range

BS Size	Bussmann	Bussmann
A2	HO7-660	NIT
A3	KO7-660	TSA
A4	L14-660	TSS
-	M14-660	TSD
B1	LO9-660	TSDS
B2	MO9-660	TST
B3	NO9-660	TLM
B4	PO9-660	TLT
C1	P11-660	TLM
C2	R11-660	TLT

Bolted Type - 415V Range

BS Size	Bussmann	Bussmann
-	EITD	EIT
-	DEO	TSFP
B1	CD	TSDC
B2	DD	TSF
B3	ED	TSF/TSK
B4	ED	TSK/TSM
-	SN11 (S)	TSMS
-	SP11 (S)	TSTS
-	SR11 (S)	TSLS
C1	EF	TSM
-	SR11	TSL

HIGHSPEED BS88 FUSES

BS Size		Bussmann		Brand 4	
TYPE	RANGE	TYPE	RANGE	TYPE	RANGE
240 Volts Range					
LCT	6-20	GSA	5-20	2.5URE	6-20
LET	25-180	GSA	25-100	2.5URGS/URZ	25-180
LMT	160-450	GS450	150-200	2.5URGG	150-200
LMT	160-450	GS450	300-500	2.5URGH	300-500
LMMT	400-900	-	-	-	-
690 Volts Range					
CT	6-20	GSB	5-20	6.6URE	6-20
ET	25-80	GSB	25-75	6.6URS	25-75
ET	25-80	GSG1000	16-55	6.6URS	16-55
EET	90-160	GSG1000	75-150	6.6URT	75-140
FM	180-350	GS1000	100-200	6.6URGL/UR	100-250
MT	160-355	GS1000	100-200	6.6URGL/UR	100-250
MMT	180-710	GS1000	300-500	-	-
MMT	180-710	GSG1000	175-350	6.6URGM/URU	175-350

HV FUSES

Appl. used in	Bussmann	Bussmann
Air	ADGHC	H2CAS
Air	ADOH6 / ADOH7	K3PGX
Air	BFGHD	H2CAS
Air	BDGHC	H2CAS
Air	AHGHC	H2CAS
Oil	OHGMA/OLGMA	KEMXO
Oil	OEFMA/OHFMA	KEBXO
VT/PT	ABWNA	VTF
VT/PT	ABCNA	VTF

Appl. used in	Bussmann	Bussmann
VT/PT	ABCNS	5xVTF
Motor Ckt.	WDOHS	K3PGX
Motor Ckt.	WDFMO/ WFFMO	K81PEX/ K81PRX
Motor Ckt.	WKFFMO	K82PEX
Motor Ckt.	WFQMO	K81SVX/ K81SRX
Motor Ckt.	WKQMO	K82SSX

LV NH DIN FUSES

BS Size	Bussmann	Bussmann	Brand 2	Brand 3
400 / 415 Volts				
SIZECOO/000	NHG000B-400	NA	NA	
SIZE 00	NHG00B-400	NA	NA	HN SIZE00
SIZE 1	NHG01-400 /NHG1-40	NA	NA	HN SIZE1
SIZE 2	NHG02-400 /NHG2-40	NA	NA	HN SIZE2
SIZE 3	NHG03-400 /NHG3-40	NA	NA	HN SIZE3
500 Volts				
SIZECOO/000	NHG000B	VSA	3NA38	NA
SIZE 00	NHG00B	VSF	3NA10	NA
SIZE 1	NHG01 /NHG1	VSK	3NA12	NA
SIZE 2	NHG02 /NHG2	VST	3NA13	NA
SIZE 3	NHG03 /NHG3		3NA14	NA
660 / 690 Volts				
SIZE 00	NHG00B-690	NA	NA	NA
SIZE 1	NH1G-690	NA	NA	NA
SIZE 2	NH2G-690	NA	NA	NA
SIZE 3	NH3G-690	NA	NA	NA

LV NH DIN BASES

Suitable for size	Bussmann		Bussmann	Brand 2	Brand 3
	TYPE	AMPS			
C00/000/00	SD00 - D	160	ISG160	3NH3030 / 3032	HB160
01/1	SD 1 - S	250	ISG250	3NH3230	HB250
02/2	SD 2 - S	400	ISG400	3NH3330	HB800
03/3	SD 3 - S	630	ISG630	3NH3430	HB800

LV BS88 BASES

BS SIZE	Bussmann			Bussmann	Brand 2	Brand 3
	FUSE TYPES	TYPE	AMPS			
Old Type						
F1	NSD/FO6	FA	32	NSH	NA	HD32H
F1	NSD/FO6	FB	32	NSP	NA	HD32P
F1	NSD/FO6	FD	32	NSB	NA	HD32B
A2	HO7 / AAO / FO7	HA	32	SM32H	NA	HK32H
A2	HO7 / AAO / FO7	HD	32	SM32B	NA	HK32B
A3	TO7 / BAO / KO7	KA	63	SM63H	NA	HK63H
A3	TO7 / BAO / KO7	KD	63	SM63B	NA	HK63B
A4	L14 / CEO / DEO@ / M14@ / KL14	LA	125	SM125H	NA	HK125H
A4	L14 / CEO / DEO@ / M14@ / KL14	LD	125	SM125B	NA	HK125B
	M14@ / KL14					
New Safeloc Type						
F1	NSD / FO6	NNSF	32	SC32H	3NW 32	NA
					NNSF	
F2	ESD	ENSF	63	SC63H	NA	NA
New Range - Cam Master						
A2	HO7 / AAO / FO7	CM32F	32		3NW CM32F9	NA
A3	TO7 / BAO / KO7	CM63F	63		3NW CM63F9	NA
	OSD	CM100F	100		3NW CM100F9	NA

@ - Upto 125A only

- The chart is intended for guidance purpose only, considering physical replaceability
- In identical operating condition, Bussmann fuse can be used to achieve similar performance
- Other makes may not necessarily have identical performance. Relevant data like rated voltage, breaking capacity, let thru' current, etc. also need to be evaluated while evaluating fuse performance

w.e.f from 16th March, 2026



State-of-the-art manufacturing facility, Pondicherry

America | Europe | Middle East | Africa | Asia Pacific

Electrical standards and certifications



PRICE :

- For items marked (#), prices available on request.
- Prices are subject to change without prior notice.
- This Price list supersedes all previous Price Lists.
- Price prevailing at the time of dispatch will only be applicable.
- For prices of any special products not listed here, please contact us
- Prices are Ex-Pondicherry, exclusive of packing, forwarding, freight & insurance.
- Company reserves the right to issue amendments which may arise due to any errors in the Price List

TAXES AND DUTIES :

- All prices in this document are inclusive of GST.
- Order Postponement or cancellation is not allowed.
- For all shipments, orders to be in multiples of the carton quantity.
- All prices are in Rupees (₹) per individual item unless stated otherwise.

This price list is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Eaton reserves the right, without notice, to change design or construction of any products or discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this price list. Once a product has been selected, it should be tested by the user in all possible applications. The information contained in this price list is correct at the time of publication, but we reserve the right to supply products differing in construction or performance.

For more information, please reach out to our Eaton sales representative.

w.e.f from 16th March, 2026

[illegible]

About EAT•N

Eaton is an intelligent power management company dedicated to protecting the environment and improving the quality of life for people everywhere. We provide sustainable solutions that help our customers manage electrical and mechanical power—more safely, efficiently, and reliably. By capitalizing on the global growth trends of electrification and digitalization, we are accelerating the planet's transition to renewable energy, solving the world's most urgent power management challenges, and building a more sustainable society for today and generations to come.

Eaton was founded in 1911 and has continuously evolved to meet the changing needs of industries worldwide. In 2025, our revenues reached nearly \$27.4 billion, and we serve customers in more than 160 countries. Eaton has approximately 92,000 employees globally. The company first established a presence in the Asia Pacific region in the 1970s. Since then, our presence has grown significantly, with a fast-expanding network of sales and marketing offices, manufacturing plants, service centers, and research facilities in the region.

Today, we have nearly 17,000 employees, 6 R&D centers, and operate 34 manufacturing facilities across countries and regions including China, India, Japan, South Korea, Singapore, Indonesia, Thailand, the Philippines, and Australia for all of Eaton's distinct business segments.

Operating in
160+
countries

92,000+
employees

100+
years of
experience

\$27.4
BILLION IN
SALES 2025

18,000+
patents

A legacy of innovation

We make stronger together work.*

US-focused power
distribution
and control business

Power quality and
datacenter market

Global geographic
expansion

Built scale

Extended
capabilities

Scaling
Precision



POWERWARE

MOELLER



INNOVATIVE SWITCHGEAR

ULUSOY

TRIPP-LITE

PDI

HUYU

COBHAM

ALFA LOMAS

green motion

Royal POWER SOLUTIONS

EXERTHERM

1979 1994

2004

2008

2013

2019 - 2021

2022-2025



We have built our capabilities and expanded through key acquisitions and partnerships...

© 2025 Eaton. All rights reserved..

Contact Eaton today to learn how the Eaton
can Transform your power Infrastructure

Visit Eaton.com/in for more information

Eaton Power Quality Pvt. Ltd. 2, EVR Street, Sedarpet Industrial Estate Pondicherry - 605111 | Tel: +91 413 2672000

Specifications subject to change without notice. ©2025 Eaton Corporation. All rights reserved.



Powering Business Worldwide

Eaton.com/in